

## WILLEMIN MACODEL W 508 MT

**Kind :** Turn-mill center  
**Brand :** WILLEMIN MACODEL  
**Model :** W 508 MT  
**Year :** 2007  
**Serial Nr:** 104  
**Stock Nr :** 10495



### TECHNICAL DETAILS

- Number of axes	: 5
- Number of spindles	: 2
<b>MAIN SPINDLE</b>	
- Spindle speeds	: 6000 [rpm]
- Max. bar diameter	: 42 [mm]
- C axis indexing precision	: 0.0001 [°]
<b>COUNTER-SPINDLE</b>	
- Spindle speeds	: 6000 [rpm]
- Max. bar diameter	: 42 [mm]
<b>CLAMPING DEVICE</b>	
- 2 Jaws chuck	: 2 Jaws chuck
- Pneumatic clamping	: Pneumatic clamping
<b>TURNING-MILLING SPINDLE</b>	
- X/Z stroke	: 450/425 [mm]
- Y stroke	: 200 [mm]
- B Axis stroke	: -15/+100 [°]
- B axis indexing precision	: 0.0001 [°]
- Tool type	: HSK-E40
- Spindle speeds	: 30000 [rpm]
- Spindle power	: 10/15 [kW]
<b>TOOL CHANGER</b>	
- Auto. Tool Changer type	: Loading arm
- Tool magazine capacity	: 48
<b>POWER SUPPLY</b>	

**Kind : Turn-mill center**

**Brand : WILLEMIN MACODEL**

**Model : W 508 MT**

**Year : 2007**

**Serial Nr: 104**

**Stock Nr : 10495**

- Supply voltage : 400 [V]

- Total installed power : 35 [kVA]

**WEIGHT & DIMENSIONS**

- Machine floor space : 3150 X 2650 [mm]

- Machine height : 2600 [mm]

- Machine weight : 2500 [kg]

**MACHINE HOURS**

- Number of working hours : 28423 [h]

**EQUIPMENT**

- CNC : Fanuc 31i-model A5

- Interactive programming

- 3 colors status lamp

- Coolant tank

- Tailstock option with counterspindle

- Spindle cooling unit

- Parts catcher

- Bar loader : LNS QUICK LOAD SERVO III

\* NB : working order not guaranteed. To have it checked by a qualified organization of the buyer.

- hydraulic Unit